Comfort and Performance for your Active Lifestyle









The Victory® series line of mobility scooters offer a perfect balance of style, comfort and performance for your active lifestyle. The Victory® 9 features onehand feather touch disassembly, wraparound delta tiller, 300 lb. weight capacity, a per charge range up to 13 miles and a maximum speed up to 5.3 mph. Standard features include, 9" solid tires, LED pathway light, LED battery meter, and a front basket. Available in Viper Blue and Candy Apple Red.











Specifications 3W:SC609 4W:SC709

Weight Capacity	300 lbs.
Maximum Speed ¹	Up to 5.3 mph
Ground Clearance ³	3W: 1.8" at transaxle, 1.4" at anti-tip, 2.7" at side deck 4W: 1.8" at transaxle, 1.4" at anti-tip, 2.1" at motor bracket bolt
Turning Radius ³	3W: 40.25" 4W: 51.5"
Overall Length ³	3W: 43.5" 4W: 45.5"
Overall Width³	3W: 22.25" 4W: 22.5"
Seat-to-Ground Height	19.25"-20.75"
Seat-to-Deck Height	17.25"-18.75"
Front Tires	3W: 3" x 8" solid 4W: 3" x 9" solid
Rear Tires	3" x 9" solid
Suspension	N/A
Range Per Charge ^{1,2}	Up to 13 miles
Total Weight Without Batteries ^{3,7}	3W: 117 lbs. 4W: 131 lbs.
Heaviest Piece When Disassembled ³	3W: 48 lbs. (front section) 4W: 59 lbs. (front section)
Standard Seating	Foldable molded plastic Weight: 28 lbs. Material: Black Vinyl Dimensions: 18" width, 17" depth
Drive System	Rear-wheel drive, sealed transaxle with 24-volt DC motor
Dual Braking System	Electronic, regenerative and electromechanical
Battery Requirements ^{3,4,5}	Size: (2) U-1standard Weight: 24 lbs. each
Battery Charger	3.5-amp, off-board
Colors	

Candy Apple Red Viper Blue

HCPCS Code: K0800 (Group 1, Standard)

- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire
- condition. This specification can be subject to a variance of (+ or -) 10%.

 Tested in accordance with ANSI/RESNA, MC Vol2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 3 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
- 4 AGM or gel cell type required.
- 5 Battery weight may vary based on battery manufacturer.
- 6 Includes standard seat weight.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of +

Features

- Exclusive one-hand feather touch disassembly provides the ultimate quick transport system
- Delta tiller with wraparound handles
- Exclusive stylish, lightweight, non-scuffing, black, low-profile tires
- Easy-to-read LED battery meter
- Long-lasting, high-intensity LED headlight offers optimal pathway illumination
- Lightweight pinchless hinge seat eight position rotation, sliders and viscoelastic foam inserts for increased comfort
- Easy-grip tiller adjustment knob
- Easy access tiller-mounted charger port

Accessories

- Cane/crutch holder (3" single, 3" double)
- Cell phone holder
- Cup holder
- Double crutch holder
- Forearm crutch holder
- Lap belt (50", 60", 70")
- Oxygen tank holder
- Quad cane holder
- Rear basket
- Rearview mirror
- Saddlebag
- Safety flag
- Walker holder
- Weather cover
- Wishbone crutch holder
- XLR USB charger

ptional Seating

- High back deluxe contour seat
 - 18" x 18" 18"x 20"

Military Patches





Find a compatible lift for your vehicle online: PRIDEMOBILITY.COM/LIFT-FINDER











or -3 %. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections.