

# PRODUCT DATA

## POLYURETHANE VARNISH



### Type

A Mineral Turpentine Soluble Polyurethane Alkyd Resin-based Interior Varnish.

### Appearance

Titanium Polyurethane Varnish is a clear coating available in gloss, satin and matt finishes and dries to the applicable appearance.

### Properties and Uses

Titanium Polyurethane Varnish is only suitable for use internally. Due to the product being based on a polyurethane alkyd resin, it has excellent hardness, slip and mar resistance and is suitable for use on interior wooden furniture, wooden kitchen cupboards, etc.

### Surface Preparation

Essential for good paint performance is a substrate that has been properly cleaned and prepared.

### Application Instructions

These instructions are issued as an aid in determining correct surface preparation, mixing and application procedure and should be closely followed to obtain maximum service from the material.

#### 1. New Uncoated Timber

- (a) Apply one coat of Titanium Polyurethane Varnish thinned 10% with Mineral Turpentine and allow to dry for a minimum of 16 hours.
- (b) Sand lightly and apply 2 coats of Polyurethane Varnish as supplied, sanding between coats and allowing a minimum drying time of 16 hours between coats.

#### 2. Previously Varnished Timber

- (a) Sand lightly.
- (b) Apply 2 coats of Polyurethane Varnish as supplied, sanding between coats and allowing a minimum drying time of 16 hours between coats.

<b><u>Application Method:</u></b>	Brush or spray.
<b><u>Spreading Rate:</u></b>	± 10m <sup>2</sup> per litre.
<b><u>Drying Time:</u></b>	Surface dry 4 hours, hard dry 16 hours at 25°C.
<b><u>Cleaning of Utensils:</u></b>	Mineral Turpentine.
<b><u>Packaging Sizes:</u></b>	5 L and 1 L
<b><u>Colour Range:</u></b>	Clear only.