



◆ SPECIFICATION

Model NO.	KDRGMHV20HTC200F	KDRGMHV20HTC200FS	KDRGMHV20HTC200ESL	KDRGMHV20HTC200ESP
Video Output Mode	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS
Camera				
Image Sensor	F23	IMX323	IMX307	IMX327
Image Resolution	1080P	1080P	1080P	1080P
Effective Pixels	1920*1080	1920*1080	1920*1080	1920*1080
TV System	PAL/NTSC			
Electronic Shutter	1/25s~1/50,000s , 1/30s~1/60,000s			
S/N Ratio	≥50dB			
Scanning System	Progressive Scan			
Lens				
Focus Length	Board Lens 3.6mm	Board Lens 3.6mm	Board Lens 3.6mm	Board Lens 3.6mm
Focus Control	Fixed	Fixed	Fixed	Fixed
Lens Type	Fixed	Fixed	Fixed	Fixed
Pixels	3M Pixels	3M Pixels	3M Pixels	3M Pixels
Auto Iris Support	NO	NO	NO	NO
Night Vision				
Infrared LED	14μ x 18PCS			
Infrared Distance	20M			
IR Status	Under 10 Lux by CDS	Under 10 Lux by CDS	/	/
IR Power On	CDS Auto Control	CDS Auto Control	Smart IR control	Smart IR control
Camera Features				
Starlight	/	/	YES	YES
Day/Night	YES	YES	YES	YES
OSD Menu Language	YES	YES	YES	YES
White Balance	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL
Gain Control	AUTO	AUTO	AUTO	AUTO
Noise Reduction	3DNR	3DNR	3DNR	3DNR
Picture Adjustment	YES	YES	YES	YES
WDR	YES	YES	YES	YES
OSD Support	YES	YES	YES	YES
UTC	YES	YES	YES	YES
Dip Switch	YES	NO	NO	NO
General				
Housing	IP66			
Bracket	NO			
Dual Voltage	NO	NO	NO	NO
IR Cut Filter	YES			
Heater	NO	NO	NO	NO
Audio	NO	NO	NO	NO
Operation Temperature	-10℃ ~ +50℃ RH95% Max			
Storage Temperature	-20℃ ~ +60℃ RH95% Max			
Power Source	DC12V±10%,550mA			
Dimension	∅ 89 x 76(H) mm			
Weight	450g			

RGM Digital