



◆ SPECIFICATION

Model NO.	KDRGMSL20HTC200FE	KDRGMSL20HTC200F	KDRGMSL20HTC200ESL	KDRGMSL20HTC200ESP
Video Output Mode	AHD/TVI/CVI: 2M@30fps/25fps	AHD/TVI/CVI: 2M@30fps/25fps	AHD/TVI/CVI: 2M@30fps/25fps	AHD/TVI/CVI: 2M@30fps/25fps
Camera				
Image Sensor	1/3" CMOS Sensor	1/2.9" CMOS Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Image Resolution	2M:1920*1080	2M:1920*1080	2M:1920*1080	2M:1920*1080
TV System	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC
Electronic Shutter	Auto	Auto	Auto	Auto
Scanning System	Progressive Scan	Progressive Scan	Progressive Scan	Progressive Scan
Lens				
Focus Length	Board Lens 3.6mm	Board Lens 3.6mm	Board Lens 3.6mm	Board Lens 3.6mm
Focus Control	Fixed	Fixed	Fixed	Fixed
Lens Type	Fixed	Fixed	Fixed	Fixed
Night Vision				
IR Cut Filter	YES	YES	YES	YES
Infrared LED	14μ x18PCS	14μ x18PCS	14μ x18PCS	14μ x18PCS
Infrared Distance	20M	20M	20M	20M
IR Status	AGC Auto Control	AGC Auto Control	AGC Auto Control	AGC Auto Control
Camera Features				
Starlight	/	/	YES	Super Starlight
Day/Night	YES	YES	YES	YES
OSD Menu Language	YES	YES	YES	YES
WDR	DWDR	DWDR	YES	YES
UTC	YES	YES	YES	YES
White Balance	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL
Noise Reduction	DNR	3DNR	3DNR	3DNR
Gain Control	AUTO	AUTO	AUTO	AUTO
General				
Housing	IP66	IP66	IP66	IP66
Bracket	NO	NO	NO	NO
Operation Temperature	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%,550mA	DC12V±10%,550mA	DC12V±10%,550mA	DC12V±10%,550mA
Dimension	∅ 94.5x76(H)mm	∅ 94.5x76(H)mm	∅ 94.5x76(H)mm	∅ 94.5x76(H)mm
Weight	450g	450g	450g	450g

RGM Digital

No. 100, Section 1, Taiwan Boulevard, Central District, Taichung City, Taiwan

Tel. No.: 886-4-2561-2199

Homepage: <http://www.rgm-digital.com>

Email: sales@rgm-digital.com