



◆ SPECIFICATION

Model NO.	IPRGMDJ5XHHL200	IPRGMDJ5XHL200	IPRGMDJ5XHP200
Camera			
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Resolution	2MP 1080P	2MP 1080P	2MP 1080P
Effective Pixels	1945(H)*1097(V)	1945(H)*1097(V)	1945(H)*1097(V)
Compression	H.264/H.264+/H.265/H.265+ /JPEG/AVI /MJPEG	H.264/H.264+/H.265/H.265+ /JPEG/AVI /MJPEG	H.264/H.264+/H.265/H.265+ /JPEG/AVI /MJPEG
TV System	PAL/NTSC	PAL/NTSC	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
Minimum Illumination	0.005Lux	0.005Lux	0.002Lux
S/N Ratio	≥52dB	≥52dB	≥52dB
Scanning System	Progressive	Progressive	Progressive
Video Output	Network	Network	Network
Reset Button	Optional	Optional	Optional
Lens			
Focus Length	2.7-13.5mm	2.7-13.5mm	2.7-13.5mm
Focus Control	Auto	Auto	Auto
Lens Type	Auto	Auto	Auto
Pixels	2M	2M	2M
Night Vision			
Infrared LED	42μ x 4PCS	42μ x 4PCS	42μ x 4PCS
Infrared Distance	30M	30M	30M
IR Status	Auto Control	Auto Control	Auto Control
IR Power On	Auto Control	Auto Control	Auto Control
Network			
Ethernet	RJ-45 (10/100Base-T)	RJ-45 (10/100Base-T)	RJ-45 (10/100Base-T)
Wireless	/	/	/

Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP, DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP, DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP, DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support ONVIF 2.4	Support ONVIF 2.4	Support ONVIF 2.4
P2P	YES, Support QR Code	YES, Support QR Code	YES, Support QR Code
POE	Optional, Support IEEE 802.3af	Optional, Support IEEE 802.3af	Internal, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)	0.3S (Within the Lan)	0.3S (Within the Lan)
Main Stream 1	2304*1296@20fps	2048*1536@15fps	2048*1536@15fps
Main Stream 2	1920*1080@30fps	1920*1080@30fps	1920*1080@30fps
Main Stream 3	1280*720@30fps	1280*720@30fps	1280*720@30fps
Sub Stream 1	720*480@20fps 720*480@30fps	720*480@15fps 720*480@30fps	720*480@15fps 720*480@30fps
Sub Stream 2	/	/	/
Sub Stream 3	/	/	/
Tri Stream	352*288@20fps 352*288@30fps	352*288@15fps 352*288@30fps	352*288@15fps 352*288@30fps
IE Brower	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53), Mac Safari(lower than version 12)	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53), Mac Safari(lower than version 12)	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53), Mac Safari(lower than version 12)
Smart Phone	iPhone, iPad, Android, Android Pad	iPhone, iPad, Android, Android Pad	iPhone, iPad, Android, Android Pad

Camera Features

Day/Night	Color/ B&W (IR-CUT)	Color/ B&W (IR-CUT)	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control), Video Tampering	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control), Video Tampering
Full Starlight	/	/	/
Corridor Pattern	Support	Support	Support
Defog Mode	Support	Support	Support
ROI	Support	Support	Support
BLC	Support	Support	Support
HDR	/	/	/
WDR	WDR: 96dB	WDR: 96dB	WDR: 96dB
Motion Detection	Support	Support	Support
Privacy Masking	3 Rectangular Zone	3 Rectangular Zone	3 Rectangular Zone
Recording Mode	NVR/CMS/Web	NVR/CMS/Web	NVR/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands,Czech, Vietnamese		

Interface

Audio	Optional	Optional	Optional
Alarm	/	/	/

SD Card Slot	Optional, Support Max 512GB	Optional, Support Max 512GB	Optional, Support Max 512GB
RS485	/	/	/
General			
Housing	IP66	IP66	IP66
Anti-cut Bracket	NO	NO	NO
IR Cut Filter	YES	YES	YES
Operation Temperature	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%,950mA	DC12V±10%,950mA	DC12V±10%,950mA
Dimension	φ159 x 132(H)mm	φ159 x 132(H)mm	φ159 x 132(H)mm
Weight	1.4Kgs	1.4Kgs	1.4Kgs

RGM Digital

No. 100, Section 1, Taiwan Boulevard, Central District, Taichung City, Taiwan

Tel. No.: 886-4-2561-2199

Homepage: <http://www.rgm-digital.com>

Email: sales@rgm-digital.com