



◆ SPECIFICATION

Model NO.	RGMZAF105
<b>Mechanical</b>	
Housing	Stainless steel 304 or 316L
IP	IP68
Cable thread hole	2pcs G3/4 or NPT3/4
Sun-shield	No
Wiper	No
<b>Electrical</b>	
Voltage	AC85V~AC265V or DC24V or AC24V
Power	8W
<b>Ambient</b>	
Ambient Temperature	25 to +60°C
Air pressure	80Kpa to 106Kpa
Relative Humidity	≦95% (no condensation)
<b>Network</b>	
Network Interface	1pcs of RJ45, support 10M/100M/1000M
Video Compression	H.264 main profile / MJPEG
Audio Compression	G.722.1/ G.711-a law/ G.711-u law/MP2L2/G.726
Voice Intercom	Support
Stream	Support three streams
Internet Protocol	IPv4/IPv6,HTTP,HTTPS,802.1x,Qos,FTP,SMTP,UPnP,SNMP
Time Display	Support
Standard	ONVIF, CGI, GB/T28181, PISA
IE browser	Support IE7 or above, Google, Firefox, Apple
Security	Password protection, Multiple access control
<b>Camera</b>	
Image Sensor	1/2.7" progressive scan, CMOS
Effective pixel	5MP
Min. Illumination	Colour: 0.01Lux (F1.6, AGC ON)
Day& Night	Auto/ Color/ BW
Optical zoom	2.8 ~ 12mm, motorized zoom lens
Effective Pixels	2592x1944
Angle of View	112.7° ~ 28.1°(H) 60.1° ~ 15.4°(V)
MOD	10mm~1500mm(wide -tele)
<b>General</b>	
Cable	integrated cable
Size	390*163*170mm
Weight	8.1kg
Mounted	wall, pole
Wall bracket	ZAZ100B
<b>ZAZ100B Wall Bracket</b>	
<b>General</b>	
Material	Stainless steel 304 or 316L
Flexible Joint	Yes
Max Loading	100kg
Weight	2.8kg