



◆ SPECIFICATION

Model NO.	RGMAC02
Package	
Camera	1pcs
Adaptor	1xDC 12V 1A
Camera	
Image Sensor	1/2.9"COMS sensor
Resolution	2MP 1080P
Effective Pixels	1920(H)*1080(V)
Compression	H.265
Electronic Shutter Time	Auto (1 / 12s~1 / 100000s)
S/N Ratio	40dB
Scanning System	Progressive
Video Output	Wireless network
Reset Button	Yes
LENS Type	
Focus Length	2.8mm F2.0
Focus Control	Fixed
Lens Type	Fixed
Pixels	2M Pixels
Night Vision	
Infrared LED	14μ x16PCS+14μ x 32PCS White light
Infrared Distance	10~15M

IR Status	CDS Auto Control
IR Power On	Auto Control
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP、UDP、HTTP、DDNS、DHCP、FTP、NTP
ONVIF	/
P2P	Support
POE	/
Main Stream 1	1920*1080@25fps
Main Stream 2	/
Main Stream 3	/
Sub Stream 1	640*360@25fps
Sub Stream 2	/
Sub Stream 3	/
Tri Stream	/
IE Brower	/
Smart Phone	support
Wireless	
Antena	3dbi
Hotspot	Support
Wi-Fi	Wi-Fi(IEEE802.11b/g/n)
WIFI Range	No obstacles 350m Max.
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Minimun Illumination	0.01 Lux
Image Config	YES
Corridor Pattern	/
ROI	/
Defog Mode	/
BLC	/
HDR	/
3DNR	Support

DWDR	Support
Motion Detection	Support
Privacy Masking	/
Recording Mode	SDcard
Language	Chinese、English

Interface

Audio	2-Way Audio
Alarm	Motion Detection
SD Card Slot	Support Max 128G

General

Housing	plastic
Bracket	/
IR Cut Filter	YES
Operation Temperature	-10°C ~ +50°C RH75% Max
Storage Temperature	-20°C ~ +60°C RH75% Max
Size	227(W)x105(H)x147(D)mm
Weight	0.52kg

RGM Digital

No. 100, Section 1, Taiwan Boulevard, Central District, Taichung City, Taiwan

Email: sales@rgm-digital.com

Homepage: <http://www.rgm-digital.com>