



◆ SPECIFICATION

Model NO.	RGMAC04
Package	
Camera	1pcs
Adaptor	1xDC 12V 1A
Camera	
Image Sensor	1/2.9" COMS sensor
Resolution	2MP 1080P
Effective Pixels	1920(H)*1080(V)
Compression	H.265
Electronic Shutter Time	Auto (1 / 12s~1 / 100000s)
S/N Ratio	40dB
Scanning System	Progressive
Video Output	Wireless network
Reset Button	Yes
PTZ	
Horizontal Rotation Range	0~270°
Tilt Rotation Range	0~90°
LENS Type	
Focus Length	2.8mm F2.0
Focus Control	Fixed
Lens Type	Fixed
Pixels	2M Pixels

Night Vision

Infrared LED	14μ x 8PCS
Infrared Distance	10-15m (Depending On Environment)
IR Status	CDS Auto Control
IR Power On	Auto Control

Network

Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP、UDP、HTTP、DDNS、DHCP、FTP、NTP
ONVIF	/
P2P	Support
POE	/
Main Stream 1	1920*1080@25fps
Main Stream 2	/
Main Stream 3	/
Sub Stream 1	640*480@25fps
Sub Stream 2	/
Sub Stream 3	/
Tri Stream	/
IE Brower	/
Smart Phone	support

Wireless

Antena	3dbi
Hotspot	Support
Wi-Fi	Wi-Fi(IEEE802.11b/g/n)
WIFI Range	No obstacles 350m Max.

Camera Features

Day/Night	Color/ B&W (IR-CUT)
Minimun Illumination	0.01 Lux
Image Config	YES
Corridor Pattern	/
ROI	/
Defog Mode	/

BLC	/
HDR	/
3DNR	Support
DWDR	Support
Motion Detection	Support
Privacy Masking	/
Recording Mode	SDcard
Language	Chinese, English

Interface

Audio	2-Way Audio
Alarm	Motion Detection
SD Card Slot	Support Max 128G

General

Housing	plastic, IP65
Bracket	Support
IR Cut Filter	YES
Operation Temperature	-10°C ~ +50°C RH75% Max
Storage Temperature	-20°C ~ +60°C RH75% Max
Size	195(W)x100(H)x190(D)mm
Weight	0.72kg

RGM Digital

No. 100, Section 1, Taiwan Boulevard, Central District, Taichung City, Taiwan

Email: sales@rgm-didigital.com

Homepage: <http://www.rgm-digital.com>