



GLASSGO PAINTS

BONDING LIQUID DATA SHEET

DATE ISSUED: 2018-01-31

SECTION 1. MANUFACTURER

Glassgo paints

SECTION 2. DESCRIPTION

Product Name: Bonding liquid

SECTION 3. PRODUCT BENEFITS

A versatile clear sealer. Excellent penetration into excessively porous surfaces. Provides adhesion to gypsum plaster for solvent and water base topcoats.

SECTION 4. PREPERATION

Ensure that all surfaces are clean, free from dust, oil, grease or any other contaminants

SECTION 5. TECHNICAL DATA

Type	: Medium oil system
Gloss Level	: Satin
Re Coating Time	: 8 Hours
Viscosity	: RFU
Practical Spread Rate	: 4 - 6 m ²
Specific Gravity	: 0.8 - 0.82
Solid by volume	: 17.35%
Solid by Mass	: 21.39%
Drying Time	: Surface dry 8 hours
Recommended DFT	: 5 - 10 microns per coat. 2 Coats Recommended
Flashpoint	: 21 C

SECTION 6. COLOUR RANGE

Clear

SECTION 7. METHODS OF APPLICATION

Brush, roller and conventional spray

SECTION 8. THINNING

Not recommended

SECTION 9. CLEAN UP

Turps / Enamel thinners

SECTION 10. PRECAUTION

Ensure good ventilation during application and drying

SECTION 11. PACKAGING

1L, 5L, 20L, 200L