



GLASSGO PAINTS

WATERBASE PRIMER

DATE ISSUED: 2019-01-31

SECTION 1. MANUFACTURER

Glassgo paints

SECTION 2. DESCRIPTION

Product name: Self priming water base acrylic polymer

SECTION 3. PRODUCT BENEFITS

A good quality water base self priming zinc phosphate primer with good adhesion to metal, tin roofs, and concrete.

SECTION 4. PREPERATION

Ensure that surfaces are clean, free from all contaminants and poorly adhering materials such as: Previous paint, dirt & oil. It is crucial that all surfaces are properly dry and suitably abraded before application.

SECTION 5. TECHNICAL DATA

Type	: Acrylic polymer
Gloss Level	: Matt to semi sheen
Re Coating Time	: 5-6 Hours
Viscosity	: 80-90 ku
Practical Spread Rate	: 4-6 Sqm/1L
Specific Gravity	: 1.1 - 14.23
Solids by volume	: 22.63%
Solids by Mass	: 33.30%
Drying time	: Touch dry 30 minutes. Surface dry 2 Hours
Recommended DFT	: 30 microns per coat

SECTION 6. COLOUR RANGE

Black and charcoal grey. (Standard, no colour mixing)

SECTION 7. METHODS OF APPLICATION

Brush, roller and airless spray.

SECTION 8. THINNING

30 - 40% water

SECTION 9. CLEAN UP

Water

SECTION 10. PRECAUTION

Goggles and respirators to be worn in confined areas

SECTION 11. PACKAGING

5L, 20L, 200L

