



GLASSGO PAINTS

EGGSHELL ENAMEL DATA SHEET

DATE ISSUED: 2018-01-31

SECTION 1. MANUFACTURER

Glassgo paints

SECTION 2. DESCRIPTION

Product name: Eggshell enamel

SECTION 3. PRODUCT BENEFITS

A high hiding, low gloss durable finish for interior and exterior use. Ideal for kitchens, bathrooms and passages where cleaning is often done.

SECTION 4. PREPERATION

Ensure surfaces are clean, free from all contaminants and poorly adhering materials such as: Previous paint, dirt & oil. It is crucial that all surfaces are properly dry and suitably abraded before application. Always use universal undercoat before painting previous painted surfaces.

SECTION 5. TECHNICAL DATA

Type	: Synthetic alkyd resin
Gloss Level	: Eggshell non-gloss
Re Coating Time	: Overnight (12-16 hours)
Viscosity	: 70-75 ku
Practical Spread Rate	: 8-10 SQM per 1litre
Specific Gravity	: 1.3 - 1.4
Solids by volume	: 50%
Solids by Mass	: 67.5%
Drying time	: Touch dry 4-6 hours. Hard dry 16-18 hours
Recommended DFT	: 30 microns per coat
Flashpoint	: 25 Degrees C

SECTION 6. COLOUR RANGE

Wide range of colors from the colorworks tinting system.

SECTION 7. METHODS OF APPLICATION

Brush, roller or spray.

SECTION 8. THINNING

White spirit

SECTION 9. CLEAN UP

Lacquer thinner

SECTION 10. PRECAUTION

Goggles and respirators to be worn in confined areas

SECTION 11. PACKAGING

1L, 5L, 25L, 200L

