

ABSOLUTELY ECO-FRIENDLY



**GREENCOAT™**  
ECO PAINT

**ROOF & POND SEALER**

## TECHNICAL AND MATERIAL SAFETY DATA SHEET

### DISCLAIMER AND IMPORTANT SAFETY NOTICE

To the best of our knowledge the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. User must contact GREENCOAT before ordering to ensure the correct products are used for application. No guarantee of accuracy is given nor implied. We guarantee that all GREENCOAT products have undergone quality control procedures to conform to GREENCOAT quality control standards. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any, is limited to the replacement of products. Prices and cost data, if shown, are subject to change without prior notice. The factory will NOT be responsible for damage or loss if application is not done by GREENCOAT trained applicators or if GREENCOAT specifications are not adhered to. It is the customers' responsibility to ensure they familiarize themselves with the correct application methods and ask for help from GREENCOAT. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY GREENCOAT, EXPRESSOR IMPLIED, STATUTORY, BY OPERATION OF LAW OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

### SUPPLIER IDENTIFICATION AND INFORMATION

Manufacturer name	Address of	GREENCOAT
manufacturing	Tel number	7 Vuyisile Mini Street, Bethal, 2310 071 482 2029
Fax number		017 647 6011
Email		admin@greencoatpaint.co.za

## PRODUCT IDENTIFICATION

Product name	GREENCOAT Roof & Pond Sealer Clear/White + Standard Colours
Product Description	Roof & Pond Sealer is a water-based, fire retardant, waterproofing and an elastomeric sealant. This product is ready for application and is used to line electric cables and water pipes. It is also used to fill and seal cracks and joints in both metal and concrete surfaces, which ultimately prevents water penetration. When the product is cured, it forms a tough, highly durable, flexible seal that has ultimate protection properties and can tolerate thermal, shrinkage movements. A satin finish is available in white, standard colours and tintable pastel base colours. The standard colours that are available are Charcoal, Medium Grey, Light Grey, Modern Red, Modern Brown, Terracotta, Black, Green, and White.
Principal Characteristics	<ul style="list-style-type: none"> <li>• The product has fast drying, excellent water resistance properties and excellent movement tolerance.</li> <li>• Cures to form an elastic seal and is excellent for sealing cracks and joints.</li> <li>• Stain, impact, and fire resistant.</li> </ul>
Intended use	GREENCOAT Roof & Pond Sealer Clear has sealing and adhesive properties. The product can be applied over concrete, metal, wood etc. The ideal area for application is ponds, metal roofs, parapets, dam, gutters, down pipes, concrete roofs, pre-cast panel walls, glazing etc.

## COMPOSITION

TECHNICAL DATA	
Drying Time	Touch Dry: 30 Minutes Full Cure: 24 Hours
Colour	Super white, standard colours and tintable pastel base Colours.
Thinner	Must NOT be thinned
Water Resistance	Excellent
Chemical Resistance	Excellent
Hardening Resistance	Excellent
Ultraviolet Resistance	Excellent
Spreading Rate	6 - 8 m <sup>2</sup> /l (Depending on the substrate)
Cleaner	Water
Storage	Store well sealed and at moderate temperatures.
De-canning Sizes	1 Litre 5 Litre 20 Litre
Application	Suitable to apply with brush or conventional caulking equipment.

## HAZARD IDENTIFICATION

Primary route of exposure	
Inhalation	Ensure proper ventilation during application in a confined space.
Eye contact	When in direct contact with material you need to wash out with water and seek immediate medical attention.
Skin contact	Prolonged and repeated contact cause no irritation. No specific symbols are required for the use of the products - the products are not combustible or flammable and do not have specific acute, chronic or toxic effects on humans, nor are they harmful to the natural environment when released.

## FIRST AID MEASURES

Eye contact	Flush eyes with large amount of water, if irritation persists, consult a physician.
Skin contact	Wash the skin with soap and water.
Ingestion	Drink plenty of water.

## FIRE-FIGHTING MEASURES

When applied on surfaces: Non-combustible, could act to retard the spread of flame.

Smoke toxicity index	Toxic gas factor - 1.0.
When cured (not applied)	Can burn.
Extinguishing agents	Normal foam, powder, water spray, or carbon dioxide (CO <sub>2</sub> ).

## ACCIDENTAL RELEASE MEASURES

Personal precautions	Follow normal safety precautions and if spillage occurs in a confined space, ensure there is adequate ventilation. There is no LD 50 data available for the products and the concentrations of particularly hazardous materials are so low that they are not considered a significant hazard under the recommended conditions of use.
Environmental precautions	No environmental hazard when applied to surfaces or cured (solidified). No threat to freshwater or marine life.
Methods for cleaning up	Contain the spillage with sand or earth and take up spilled material (if possible) on a non-flammable absorbent (sand, earth, diatomite, chemical binders) and put in an appropriate container. Label the container with the waste designation and dispose according to the legislation - do not use solvent.

## HANDLING AND STORAGE

Safe handling advice	Avoid direct contact with skin and eyes. Avoid inhalation and ingestion. Take personal protective measures and follow the protection and safety regulations. When working with coating products in a spray cabin, sufficient control of aerosols is unlikely and breathing apparatus such as respirators can be worn during spraying if preferred.
Measure to prevent fire	No specific preventative measures are required but keep the application area well ventilated.
Requirements for storage	Store in original containers (if possible) and keep tightly closed in a cool, dry, well-ventilated area. Although the products are not defined as dangerous goods, protect the products from direct extreme heat such as sources of ignition. Avoid direct sunlight and do not store in conditions below freeze-point.
Shelf life	±2 years if well sealed.

## EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure limit: OSHA PEL 15 mg/m (total dust), 5 mg/m (respiration fraction)

Personal protection	
Respiratory protection	Respiratory programme must be followed whenever workplace conditions warrant a respirator's use. Not required if airborne concentrations are maintained below exposure limit listed in exposure limit information.
Eye Protection	Safety glasses with impenetrable side shields are recommended.
Skin protection	Gloves may be used if required, but no known effects have been observed.

## STABILITY AND REACTIVITY

Stability	Stable when following the handling and storage recommendations.
Conditions to avoid	Avoid temperatures above 40°C, direct sunlight and below freeze point for storage conditions.
Incompatibility	None known
Hazardous decomposition	By fire - carbon dioxide (CO <sub>2</sub> ) and carbon monoxide (CO).

## PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquids
Odour	Characteristic of the specific product (faintly similar to a PVA paint product in some cases)
PH	-8 -9
Reactivity	Salt fog resistant
UV Resistance/Weathering:	75 000 hours - No visible breakdown
Density	> 1 gm/cm
Vapour density	Heavier than air
Solubility	Miscible in / with water prior to cure
Evaporation rate	< 1 water (see section 5)

## TOXICOLOGICAL INFORMATION / HEALTH EFFECTS

Acute toxicity:	No known effects - health hazard rating in group 4 (minimal) of the Recommended Practice (ARP 006: 1991) guideline
Skin contact:	No known effects
Eye contact:	Splashes can cause eye irritation
Chronic toxicity:	No known effects
Carcinogenicity:	No known effects
Mutagenicity:	No known effects
Neurotoxicity:	No known effects
Reproductive hazards:	No known effects
Additional information:	The products have not been tested, but their classifications calculated according to conventional methods from the dangerous substances regulations. The products have been used to paint aquariums that house tropical fish and ponds that house Koi fish with no effects at all. The products do not emit noxious fumes or odour during and after application.

## ECOLOGICAL INFORMATION

Aquatic toxicity	No known effects
Biodegradability	Products are considered highly biodegradable, but not tested
Bioaccumulation:	No known effects
Mobility:	Not tested
Additional information	The product is environmentally friendly with a very low VOC (Volatile Organic Compound) as tested by the Huntingdon / SWL laboratories, Report number: 261394 - 23093 and described by America as a revolutionary breakthrough.

## DISPOSAL CONSIDERATION

Disposal key	080103 - EWC waste from water-based paints.
Disposal method	Hand over empty packaging to an authorised disposal company / waste company - the waste regulations of the appropriate authorities are to be followed.

## TRANSPORT INFORMATION

ADR / FID (Road)	Not dangerous materials according to these regulations.
GGVSee / MDG (Maritime)	Not dangerous materials according to these regulations.
IATA (AIR)	Not dangerous materials according to these regulations.

## REGULATORY INFORMATION / EEC CLASSIFICATION

EEC hazard classification	None of the substances of the products are classified by the EEC as hazardous.
TSCA certification	All of the substances in the products are listed, or exempt from listing, on the TSCA.
National legislation	Pay attention to the Occupational Health and Safety Act.

## OTHER INFORMATION

All data is based on the current knowledge of GREENCOAT and describes the product with reference to safety data and is therefore not intended to guarantee certain properties.

## APPLICATION INSTRUCTIONS AND TECHNICAL DATA

These instructions are not intended to show product recommendations for specific services. They are issued as an aid in determining correct surface preparation and application procedures. It is assumed that the proper recommendations have been made. These instructions should be followed closely to obtain the maximum service from the material.

### Features Included:

- Quick drying - overcoat 30 - 60 minutes
- Excellent flexibility - will never harden
- Ultraviolet and weather resistant: 75, 000 hours +
- Good abrasion resistance
- Exceptional performance in wet weather.
- Rust prevention

- Colour fastness
- Zero flame spread

**Recommended use:** Exterior and interior walls, structural steel, piping, tank frames, rail cars, corrugated iron, offshore oil and gas stations, boats, wood, asbestos, glass fiber, copper, glass and aluminum.

**Excellent resistance to:** Acids, alkalis, water, salt solutions and solvents.

**Temperature resistance:** Minus 50°C - 180°C. At 110°C loss of gloss is observed and discoloration takes place, without loss of film integrity.

**Application:** Suitability prepared concrete, metal and any surfaces as recommended.

**Compatible Coatings:** A test patch is recommended before use of most coatings. Contact your GREENCOAT dealer for specific information.

## REQUIREMENTS FOR STORAGE AND APPLICATION

Parameter	Storage (Unopened)	Paint	Substrate	Environment
% RH (Relative Humidity)	100 % Maximum	-	Min 2°C above Dew Point	85 % Max
Temp °C Min	5°C	5°C	5°C	5°C
Temp °C Min	40°C	40°C	40°C	40°C

**Surface Preparation:** GREENCOAT Bind MUST be applied before the GREENCOAT Roof & Pond Sealer application can start. All joints, cracks and must be sound, clean and dry. Grease, oil, laitance, previous waterproofing or damp proofing materials and other contamination must be thoroughly removed. Cleaning may be done by wire brush or sandblasting. Ensure that the sealant is firmly filled into the joints or cracks to give the full strength. For shrinkage cracks or cracks that occur more than 2mm wide it is recommended that the Sealer must be mixed with washed sand.

**Application:** Suitable to apply with brush, roller and spray.



**GREENCOAT CC**  
 7 Vuyisile Mini Street, Bethal, 2310  
 Customer Service Department [admin@greencoatpaint.co.za](mailto:admin@greencoatpaint.co.za)  
 Facsimile 017 647 6011