Tractor Pull Class Rules

200LB Grace Period on all classes

Farm Stock *FARM STOCK IS FARM STOCK* NO CUT TIRES 4,500-7,500

- Floor plate required
- Fenders required if factory equipped
- Throttle must be at throttle stop at maximum RPM
- Tire size 18.4-38 Maximum

<u>9,500</u>

- Same as above except,
- Tire size 20.8-38, 18.4-42 Maximum

10,500-18,500

- RPM Limit -3000
- Floor plate required
- Fenders Required if factory equipped
- Throttle must be against stop at max RPM
- Working 3pt and PTO if factory equipped
- Must retain all factory cast parts, no sheet metal replacements
- Factory add on turbo allowed (M&W, TO4)

The <u>16,500 class</u> will be a <u>Farmers Grudge Match</u>..... (BRAGGIN RIGHTS) SUPER TROPHY if you win you must bring it back the following year and try for it again

Farm Stock Classic

<u>9,000</u>

- Stock RPM's
- Stock engine block, carb, drivetrain for that make & model
- Floor Plate required
- Duals allowed
- Throttle must be against stop at max RPM

KING OF THE KLAY

10,500 EVERYTHING ALLOWED just for a trophy. Tractors, Trucks, Bus, Moped, Jet Ski whatever you can get to #10,500

Farm Improved

**Factory add on turbo or TO4 such as 4020 or 966 is allowed in 10,000 class only as long as they retain factory add on components-intake, exhaust etc. No modifications allowed.

- Factory appearing or stock replacement block, injection pump, front end, and drivetrain
- Single Barrel updraft carb only
- All tractors must have fenders and floor plates
- All factory turbos must hook up to the exhaust and intake with no modifications
- No block spacers
- Governor required

Hot Farm

- Up to 466ci a 3x4 turbo allowed
- 466ci and up 3x3 turbo allowed
- Fuel restricted to an A pump unless factory OEM was a P pump
- No RPM limit
- Roll bar or Roll cage required
- Block, driveline/transmission, rear axle, and sheet metal must match model of manufacture
- No custom frames or front axles
- Wheelie bars required
- Working kill switch above drawbar required
- Side Shields required if running a belt driven fan (electric fan preferred)
- No intercoolers allowed
- Water injection is allowed

Open Mod

- Exhaust pipe must be cross bolted
- Roll over protection required
- Helmet and fire suit mandatory
- Must have safety blanket or scatter shield around clutch/flywheel
- Front dampener covered
- Must have breakaway switch and secondary emergency kill switch within reach of driver
- Wide front must track within rear wheels

Light Limited Super Stock

<u>6,500</u>

• Must follow WTPA rules