GENT by Honeywell

# MANUAL CALL POINTS

The new range of conventional manual call points from Gent by Honeywell simplifies installation time.



#### Description

The new conventional manual call points are designed to provide a manual alarm interface to conventional fire alarm control panels. All call points are supplied in the standard red colour and are available in semi-flush mounting or surface mounting options. The manual call points from Gent are all with a 470 Ohm resistor and Normally Open contact, complete with glass.

Both break glass, and resettable operating elements can be used in the standard unit by a yellow strip on the element which becomes visible when activated. With the addition of a hinged transparent cover the element may be protected against accidental operation. A specialist test key may be inserted into the bottom of the unit to lower the glass and release the micro-switch and thus a full functional test is achieved.

#### **Key Features**

- Fully compliant with EN54, Part 11
- Re-settable operating element option
- Weather proof IP67
- Semi-flush or surface mounting
- 470 Ohm resistor and Normally Open contact complete with glass
- Resistive and clean contact connections


| SPECIFICATION                  |                                   |                      |
|--------------------------------|-----------------------------------|----------------------|
|                                | Standard                          | Weatherproof         |
| Weight                         | 180g (130g Semi- flush)           | 240g                 |
| Current rating                 | 2A (switching only)               | 2A (switching only)  |
| Operating Voltage              | 30VDC maximum                     | 30VDC maximum        |
| Dimensions mm (H x W x D)      | Semi-flush mounted 93 x 89 x 59.5 |                      |
| Operating temperature          | -10°C to +55°C                    | -30°C to +70°C       |
| Relative humidity              | 93+ 3% non-condensing             | 0-95% non-condensing |
| Ingress Protection (IP) Rating | IP24D                             | IP67                 |

### Dimensions: Standard MCP \*

## Dimensions: Waterproof MCP

97.5mm

ר







\* Surface mounted

| CONVENTIONAL MCP WITH 470 OHM RESISTOR AND N/O CONTACT         | ORDER CODES |
|--|-------------|
| Flush MCP 470 Ohms Glass                                       | XENS-850    |
| Surface MCP 470 Ohms Re-settable                               | XENS-805    |
| Weatherproof MCP 470 Ohms resistor Glass                       | XENS-829    |
| Key Operated, Surface Mounted c/w backbox                      | XENS-807    |
| Change over contact MCP  | XENS-801    |
| NEW MANUAL CALL POINT ACCESSORIES AND SPARES                   | ORDER CODES |
| Spare Glasses for MCP XENS-800 (Pack of 10)                    | XENS-891    |
| Resettable element for XENS-800 and XENS-805 (pack of 10)      | XENS-890    |
| Hinged protective cover for use on XENS-800 range (pack of 10) | XENS-892    |
| Surface Backbox for XENS-800 range of MCP (pack of 10)         | XENS-895    |
| Replacement keys for XENS-807 K/S MCP (pack of 10)             | XENS-893    |
| Pack of test keys (pack of 10)                                 | XENS-899    |