

# Solar INVERTER



## 5000VA

- Pure sine wave solar inverter
- Detachable LCD control module with multiple communications
- Wide DC input range
- Built-in Bluetooth for mobile monitoring (Android App is available)
- Supports USB On-the-Go function
- Reserved communication port for BMS (RS485)
- Smart battery charger design for optimized battery performance
- Battery independent function
- Parallel operation up to 9 units
- Optional dual outputs for smart load management (check sales)



MODEL	MKS III 5K
<b>RATED POWER</b>	5000VA/5000W
<b>INPUT</b>	
Voltage	230 VAC
Selectable Voltage Range	170-280 VAC (For Personal Computers) 90-280 VAC (For Home Appliances)
Frequency Range	50 Hz/60 Hz (Auto sensing)
<b>OUTPUT</b>	
AC Voltage Regulation (Batt. Mode)	230 VAC $\pm$ 5%
Overload Capacity	5s@ $\geq$ 150% load; 10s@110%~150% load; 100ms @ $\geq$ 200% load
Efficiency (Peak)	93 %
Transfer Time	10 ms (For Personal Computers) 20 ms (For Home Appliances)
Waveform	Pure sine wave
<b>BATTERY</b>	
Battery Voltage	48 VDC
Floating Charge Voltage	54 VDC
Overcharge Protection	66 VDC
<b>SOLAR CHARGER &amp; AC CHARGER</b>	
Solar Charger Type	MPPT
Maximum PV Array Power	5000 W
MPPT Range @ Operating Voltage	120 ~ 430 VDC
Maximum PV Array Open Circuit Voltage	450 VDC
Maximum Solar Charge Current	100 A
Maximum AC Charge Current	100 A
Maximum Charge Current	100 A
<b>PHYSICAL</b>	
Dimension, D x W x H (mm)	140 x 295 x 468
Net Weight (kgs)	12.0
Communication Interface	USB/RS232/RS485/Bluetooth
<b>ENVIRONMENT</b>	
Humidity	5% to 95% Relative Humidity (Non-condensing)
Operating Temperature	-10°C to 50°C
Storage Temperature	-15°C to 60°C

Product specifications are subject to change without further notice.