BEST-IN-CLASS





Vivarium Consult International

Equipment & Enrichment for Research Animal Facilities







VIVARIUM -SAFE MCCU

Mobile Cage Changing Station

BEST-IN-CLASS

Low noise <52 dB(A) Operator/ Product Protection HEPA 14 Filters Electronic Height Adjustable

OPTION:

Built-in CageTalkers® technology Remote Service Support




+45 501 428 27



vivariumconsult.com







Superior operator and product protection.

Vivarium-SAFE manufactures intelligent engineered biological safety cabinets that provide clean air solutions for a wide range of applications, ranging from routine work with potentially hazardous samples to handling cytotoxic compounds.

Vivarium-SAFE provides the level of operator, product and environmental protection you need. Every cabinet is designed to make your daily work as easy and comfortable as possible. Engineered by Experience - Compact design but still best-in-class usable inner dimensions.



VIVARIUM-SAFE MCCU MOBILE CAGE CHANGING STATION

- Completely new developed unit
- Advanced technology in filters, fans as well in controller
- Super silent operation with noise level <52 dB(A)!
- EN12-469 compliant
- Full operator protection >0,42 m/s inflow with both sides open!
- Double ventilated table tops No contamination between right and left side
- High light intensity dimmable 0-1500 Lux
- Electrically elevated support, programmable for different users
- Compact design with rounded corners
- High quality silent wheels lockable
- Multiple table tops designs
- Low weight <200 kg makes it easy to move
- Easy-to-change pre-filter cassettes
- H14 filters for supply and exhaust air

Optional:

- Active carbon filter for exhaust air reducing odours
- Worldwide remote support for fast and easy service
- Autoclavable stainless steel food doser
- Battery backup for running the unit w/o electrical connection



Furthermore the system allows up to 12 months of continuous data backup. With customer approval we access the cabinet remotely wherever it is installed, requiring only open internet access. High security without managing firewalls.

SPECIAL IS OUR STANDARD

"Special is our standard" meaning that all our products can be custom made and configured to meet every specific requirement within reasonable time and budget.

We work closely with our customers to create and support biological safety cabinets that offer unmatched quality, precision and reliability with highest level of cleanability.



NOISE

Field case studies prove that Vivarium-SAFE MCCU measure <52. dB(A) due to latest filter and fan technology.



Our models are built and tested according to national and international standards including: EN 12-469, EN 61010-1



STANDARD FEATURES

Technical specifications Vivarium-SAFE MCCU

| Туре | | VS 1300 | VC 1600 |
|-------------------------------------|---|-----------------------------------|-----------------------------|
| Dimensions | | | |
| External dimensions, WxDxH | mm | 1295 x 795 x 1935-2285 | 1595 x 795 x 1935-2285 |
| Internal dimensions, WxD | mm | 1045 x 677 | 1345 x 677 |
| Front window opening | mm | 350 / 700 (open) | 350 / 700 (open) |
| Work height, standard support stand | mm | 854-1204 | 854-1204 |
| Minimum door way | mm | 800 | 800 |
| Weight | | | |
| Equipment | kg | 195 | 220 |
| Air velocity | | | |
| Vertical flow | m/s | 0.28 (adjustable 0.25 -0,38) | 0.28 (adjustable 0.25 -0,38 |
| Inflow | m/s | 0,42 | 0,42 |
| Deviation | ±% | <8 | <8 |
| Noise | | | |
| Noise level ISO3744 | dB(A) | 52 | 54 |
| Ventilation | | | |
| Down flow rate | m3/h | 710 | 920 |
| Exhaust flow rate | m3/h | 2060 | 2350 |
| Filter technology | | | |
| Main/Exhaust Type | HEPA H14 EN1822, 99,999% at 0,3 µm particle size Optional exhaust activated carbon | | |
| Light | | | |
| LED | Lux | 0-1500, dimmable | |
| Electrical data | | | |
| Voltage frequency | V/Hz | 220-240/50-60 or 110-120/50-60 | |
| Power consumption, from | W | 100 | 130 |





HOUSING SOLUTIONS

DIGITAL CAGE CARDS

EUTHANASIA AND OP TABLES

STERILE AIRHANDLING AND BARRIER TECHNOLOGY

CONSUMABLES & ACCESSORIES



+45 501 428 27



vivariumconsult.com



info@vivariumconsult.com

