









The Iris LED downlight has a choice of four reflectors: 25, 60° multi-faceted, 40° specular and 50° Satin etched and a wide range of bezels.

- Various dimming controls, emergency options and colour temperatures available
- Ideal for office, retail and hospitality lighting
- Tridonic or Philips module and driver

















Product Specification

Colour Temperature (k)	3000	4000
Colour Rendering Index (CRI)	80	
Glare Control (UGR)	>19	
McAdam SDCM	3	
Average Luminaire Efficacy	126.2	
Ingress Protection (IP)	IP20	
Average Lifespan (Hr)	55,000	
Operating Temperature Range (°C)	-25	+35

Electrical Specification

Voltage (V)	220-240
Frequency (Hz)	50-60
Electrical Protection	Class I

Tridonic Lumen Performance

Product Code	Output	Colour	Wattage	Efficacy
IRI TR LED10	1055	840	8	131.3
IRI TR LED18	1787	840	13.8	129.4
IRI TR LED24	2442	840	19.2	127.2
IRI TR LED32	3252	840	27.8	116.9


Luminaire Options

Emergency	3hr	3hr Dali	
Dimming	0-10v	Dali	Switch
Reflectors	25° 40	o° 50° 60°	0

Philips Lumen Performance

Product Code	Output	Colour	Wattage	Efficacy
IRI PH LED7	669	940	6.2	107.9
IRI PH LED12	1227	940	11.5	106.7
IRI PH LED19	1915	940	18.1	105.6
IRI PH LED26	2587	940	26.9	96.3
IRI PH LED35	3487	940	32.1	108.6
IRI PH LED49	4939	940	48	102.8

Dimensions



Diameter (mm)	130
Cut-out (mm)	110
Height (mm)	99
Weight (kg)	0.5



Options & Accessories









IP65 Bezel Frosted

IP65 Bezel Clear

IP54 Bezel Frosted

IP54 Bezel Clear







Chrome Bezel



Brushed Aluminium Bezel



Coloured Bezel Available in Red & Green



Halo Bezel Clear



IP65 Bezel Blue Available in Red & Green



Hi-Light Bezel Clear



Hi-Light Bezel Blue Available in Red & Green



Iris Bezel Frosted



Iris Bezel Blue



Iris Bezel Red



Iris Bezel Green



Drop Lens Options









Glass Clear

Glass Centre Etched

Glass Halo

Glass Etched Halo









Glass Etched

Glass Etched Halo Blue

Glass Etched Halo Red

Glass Etched Halo Green

Installation Accessories





Adaptor Ring for oversize hole

Plaster-in Kit