



Hotspot Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 [www.rustins.ltd/hotspot](http://www.rustins.ltd/hotspot)

November 2020

## PRODUCT DATA SHEET

<b>Product</b>	<b>Heatbond Stove Rope Fixative</b>
<b>Type</b>	A non-toxic fixative.
<b>Intended Use</b>	Specially formulated fixative for bonding sealing rope (fibreglass or ceramic) onto solid fuel stoves or cookers.
<b>Special Features</b>	Contains no solvents and so can be used in confined spaces, also heat resistant to 900°C.
<b>Preparation</b>	Shake the bottle vigorously before use. Ensure groove is clean and free from grease etc.
<b>Application</b>	Apply adhesive to groove with a small brush, press sealing rope firmly into place. Should you make a mistake, simply pull out sealing rope and start again.
<b>Coats</b>	N/A
<b>Drying Time</b>	Allow 15 minutes before closing doors. The heat from the appliance will do the rest. If no heat source is available, it will take longer, in which case, please allow 24 hours to fully dry.
<b>Re-coating Time</b>	N/A
<b>Application Temp.</b>	Some heat ideally.
<b>Coverage</b>	N/A
<b>Maintenance</b>	N/A
<b>Compatibility</b>	Compatible with most solid stove/cooker surfaces.
<b>Settlement</b>	Product may settle after prolonged storage which is perfectly normal. Keep container tightly closed when not in use.
<b>Shelf-life/Storage</b>	2 years if stored unopened in a cool, dry place.
<b>Hazards</b>	Not classified as hazardous to user. Keep out of reach of children.
<b>Clean-Up</b>	Clean with water while wet.
<b>Sizes</b>	30ml bottle with brush & 125ml bottle.