



Hotspot Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.ltd/hotspot

November 2020

PRODUCT DATA SHEET

Product	Slate Oil
Type	Protection and sealing oil.
Intended Use	Hotspot Slate Oil seals and protects tired looking slate, enhancing its natural beauty. It may slightly deepen the natural colour.
Special Features	The sealer repels dirt and water whilst still allowing the slate to breathe.
Preparation	Shake bottle before use. Cover and protect all carpets, fabrics, etc. Ensure surface is clean, dust and grease free. Slate Oil can be slightly thinned using white spirit.
Application	Using a soft lint-free cloth, apply Slate Oil evenly and sparingly. Buff up with a soft lint-free cloth. If too much is applied, or not polished, it can leave a streaky/patchy finish.
Coats	As required.
Drying Time	Allow 2 hours to touch dry.
Re-coating Time	Reapply as required.
Application Temp.	Ideally 15 – 25 degrees Centigrade.
Coverage	Approx. 1 sq. metre per bottle depending on end-user.
Maintenance	May need polishing from time to time.
Compatibility	It is recommended that a small inconspicuous area is tested prior to complete application.
Settlement	Shake well before use.
Shelf-life/Storage	Store in a cool, dry place. Max. 2 years.
Hazards	Flammable; do not use near naked flame. Irritating to eyes & respiratory system. Avoid contact with eyes & skin. Avoid contact with fabrics, carpets etc. Keep out of reach of children. Visit www.rustinsltd/hotspot for full SDS.
Clean-Up	Clean up with white spirit.
Sizes	100ml bottle.